

M.C.E. TECHNIK S.R.L.

Via Dante, 22

35030 Caselle di Selvazzano

PD

P.I. 00995980281

Cod.Fisc 00995980281

Tel. 049-631332

Tel. / Fax 049-630155

E-mail info@mcetechnik.it

Scheda Articolo



Codice	Descrizione	U.M.	Listino
004457	DEVIATORE BIPOLARE NERO PER CASSETTE 22x30 16A 250V 6 faston 6.3mm	NR	5.31

Dettagli Articolo

Peso Articolo 0.050

Rocker Switch R5 Series

Electrical Rating : 20A 125VAC/16A 250VAC(UL) 10A/15A/16A 250VAC(VDE) 10A 250VAC/15A 125VAC(UL)

Mechanical life: Over 30000 cycles

Electrical life: Over 10000 cycles

Contact resistance: <20m Ω

Insulation resistance: >1000M Ω High voltage resistance: >1500V 1 min.

Ambient temperature: Terminal side -20 to +85 $^{\circ}$ C

Actuating side -20 to +55 $^{\circ}$ C

Storage temperature: -30 to +80 $^{\circ}$ C Max

Atmospheric humidity: Max.85%

Actuating force: 4~8N(depends on different switch function)

Flammability: UL94 V-2 Temperature rise at the terminal: Max 30 $^{\circ}$ C (UL1054)

Solder ability of terminal: Max 350 $^{\circ}$ C, 3s

Materiali

Housing: Nylon 66

Rocker: PC & PA66

Contacts: Silver Alloy

Terminal: Brass Silver Plated

Lamp: Neon Lamp, Tungsten

Lamp Spring: SWP, SUS

Movable Arm: Brass Silver Plated

CERTIFICAZIONI EN-EC /VDE/CCC/UL