**M.C.E. TECHNIK S.R.L.**
Via Dante, 22
35030 Caselle di Selvazzano PD
P.I. 00995980281 Cod.Fisc 00995980281
Tel. 049-631332 Tel. / Fax 049-630155
E-mail info@mcetechnik.it

# Scheda Articolo




| Codice | Descrizione | U.M. | Listino |
|---|---|---|---|
| 004457 | DEVIATORE BIPOLARE NERO PER CASSETTE 22x30 16A 250V 6 faston 6.3mm | NR | 5.31 |

## Dettagli Articolo

Peso Articolo 0.050

**Rocker Switch R5 Series**

Electrical Rating : 20A 125VAC/16A 250VAC(UL) 10A/15A/16A 250VAC(VDE) 10A 250VAC/15A 125VAC(UL)
Mechanical life: Over 30000 cycles
Electrical life: Over 10000 cycles
Contact resistance: <20m?
Insulation resistance: >1000M? High voltage resistance: >1500V 1 min.
Ambient temperature: Terminal side -20 to +85â„ƒ
Actuating side -20 to +55â„ƒ
Storage temperature: -30 to +80â„ƒ Max
Atmospheric humidity: Max.85%
Actuating force: 4~8N(depends on different switch function)
Flammability: UL94 V-2 Temperature rise at the terminal: Max 30â„ƒ (UL1054)
Solder ability of terminal: Max 350â„ƒ,3s
Materiali
Housing: Nylon 66
Rocker: PC & PA66
Contacts: Silver Alloy
Terminal: Brass Silver Plated
Lamp: Neon Lamp,Tungsten
Lamp Spring: SWP,SUS
Movable Arm: Brass Silver Plated
CERTIFICAZIONI EN-EC /VDE/CCC/UL